

Reach indoor working heights of up to 6.57 metres safely and efficiently...



Lightweight. Efficient. Compact.



Versatile: suitable for indoor work on sensitive flooring, as well as for outdoor (wind rated) applications.



Easily Manoeuvrable: compact and lightweight with zero turning radius for work in tight spaces.



Increase Productivity: electric drive with reduced hydraulic fittings for increased up-time, fewer leaks and service calls.



Improve Safety: only authorised users can operate the machine. Supports safe work at inclines of up to 3%. Complies with EN 280 specifications.

CONTACT MEP HIRE

T: 0800 587 5121 E: hire@mephire.co.uk W: www.mephire.co.uk



SPECIFICATIONS



- A. Platform height (lowered) 0.8m
- B. Platform railing height 1.1m
- C. Machine height 1.9m
- D. Platform width 0.6m
- E. Platform length 1.3m
- F. Platform extension 55cm
- **G.** Machine width 76cm
- H. Machine length 1.4m
- I. Wheelbase 1.1m
- J. Ground clearance 6cm

Max indoor height	6.57m (working) - 4.57m (platform)
Max outdoor height	5m (working) - 3m (platform)
Platform capacity	227kg
Dimensions	H: 1.9m W: 76cm L: 1.4m
Number of occupants	Max 1 person (indoor and outdoor)
Lift and lower time	19 seconds (no load), 17 seconds (rated load)
Max drive height	Fully elevated
Weight	880kg
Ground bearing pressure	116psi or 8.1kg/cm²
Gradability	25%
Gradability Drive speed	25% 2.4mph (lowered) or 0.5mph (elevated)
Drive speed	2.4mph (lowered) or 0.5mph (elevated)
Drive speed Tilt rating (side-to-side)	2.4mph (lowered) or 0.5mph (elevated) 2.5 degrees (indoor) 1.5 degrees (outdoor)
Drive speed Tilt rating (side-to-side) Tilt rating (fore and aft)	2.4mph (lowered) or 0.5mph (elevated) 2.5 degrees (indoor) 1.5 degrees (outdoor) 3 degrees (indoor and outdoor)
Drive speed Tilt rating (side-to-side) Tilt rating (fore and aft) Turning radius	2.4mph (lowered) or 0.5mph (elevated) 2.5 degrees (indoor) 1.5 degrees (outdoor) 3 degrees (indoor and outdoor) Zero (indoor) 1.4m (outdoor)
Drive speed Tilt rating (side-to-side) Tilt rating (fore and aft) Turning radius Reservoir capacity	2.4mph (lowered) or 0.5mph (elevated) 2.5 degrees (indoor) 1.5 degrees (outdoor) 3 degrees (indoor and outdoor) Zero (indoor) 1.4m (outdoor) 5 litres (Hydraulic)

Telematics, Track Unit, Anti-entrapment Secondary Guarding

CONTACT MEP HIRE

T: 0800 587 5121

E: hire@mephire.co.uk W: www.mephire.co.uk

